

Journal of
Mechanics of
Materials and Structures

**DISCUSSION OF “STUDY OF VISCOELASTIC AND FRICTION
DAMPER CONFIGURATIONS IN THE SEISMIC MITIGATION OF
MEDIUM-RISE STRUCTURES”**

Julius Marko, David Thambiratnam and Nimal Perera

Volume 1, N° 8

October 2006



mathematical sciences publishers

DISCUSSION OF “STUDY OF VISCOELASTIC AND FRICTION DAMPER CONFIGURATIONS IN THE SEISMIC MITIGATION OF MEDIUM-RISE STRUCTURES”

JULIUS MARKO, DAVID THAMBIRATNAM AND NIMAL PERERA

Volume 1:6 (2006), 1001–1039

Izuru Takewaki writes:

The discussor is very interested in the paper presented by Julius Marko, David Thambiratnam and Nimal Perera. This paper includes various interesting aspects, for example, comparison of the effectiveness of various damper systems (viscoelastic, friction and hybrid), optimal damper configuration and location, and the influence of different types of earthquake ground motions on the response reduction by dampers.

The authors draw several references for readers. In the discussor’s opinion, more versatile investigations on optimal damper configuration and location have been made in the scientific community of earthquake engineering, and computing algorithms based on certain theoretical backgrounds have been proposed [Austin and Pister 1985; Takewaki 1997; Takewaki and Yoshitomi 1998; Takewaki 1999; Takewaki et al. 1999; Takewaki 2000a; Takewaki 2000b; Takewaki 2000c; Garcia 2001; Singh and Moreschi 2001; Singh and Moreschi 2002; Garcia and Soong 2002; Liu et al. 2003; Silvestri et al. 2003; Kiu et al. 2004; Park et al. 2004; Trombetti and Silvestri 2004; Xu et al. 2004; Liu et al. 2005; Tan et al. 2005; Trombetti and Silvestri 2006; Wongprasert and Symans 2004; Lavan and Levy 2005; Lavan and Levy 2006; Aydina et al. 2007]. For example, the optimal quantity and location of dampers can be obtained automatically with the help of these algorithms; the *gradient-based algorithm* is a representative one [Takewaki 1997; Takewaki and Yoshitomi 1998; Takewaki 1999; Takewaki 2000a; Takewaki 2000b; Takewaki 2000c; Takewaki et al. 1999]. It is obvious that dampers have various kinds of nonlinearities, and a time-history response analysis is often required to simulate the behaviors of structures with such dampers. However, many useful equivalent linearization techniques have been proposed [Roberts and Spanos 1990], and these techniques certainly make it possible to treat those behaviors almost theoretically. Although the equivalent linearization techniques have some limitations on the range of applicability, most of building structures are designed within this range of applicability.

The authors point out another interesting aspect, that is, the influence of different types of earthquake ground motions on the response reduction by dampers. The broad-range parametric simulation using recorded ground motions may be attractive and lead to many useful conclusions. However, it is also true that theoretical approaches enable one to capture more essential features of permanent interest even if the range of applicability is limited. For example, the concept of critical excitation or worst-case analysis

Keywords: dampers, multistory buildings, seismic mitigation, finite element techniques.

seems to provide a powerful means for overcoming the difficulties caused by uncertainties of earthquake ground motions [Drenick 1970; Shinozuka 1970; Takewaki 2000b; Takewaki 2001; Takewaki 2002a; Takewaki 2002b; Takewaki 2002c; Takewaki 2004; Takewaki 2007]. The tough and robust design may be possible using this concept [Takewaki 2000b; Takewaki 2002b; Takewaki 2007].

In closing, the discussor would like to call the attention of interested readers to the work reported in [Takewaki 1997; Takewaki and Yoshitomi 1998; Takewaki 1999; Takewaki et al. 1999; Takewaki 2000a; Takewaki 2000b; Takewaki 2000c; Garcia 2001; Singh and Moreschi 2001; Liu et al. 2003; Park et al. 2004; Silvestri et al. 2003; Trombetti and Silvestri 2004; Lavan and Levy 2005; Liu et al. 2005; Lavan and Levy 2006; Takewaki 2007] to provide a broader context for the results reported by Julius Marko, David Thambiratnam and Nimal Perera.

IZURU TAKEWAKI: takewaki@archi.kyoto-u.ac.jp

*Dept. of Urban and Environmental Engineering, Graduate School of Engineering, Kyoto University
Kyotodaigaku-Katsura, Nishikyo-ku Kyoto 615-8540, Japan*

The authors respond:

The authors would like to thank the discussor for the encouraging remarks and the valuable comments. We reviewed the work by Austin, Pister, Takewaki, Yoshitomi, Singh, Moreschi, Garcia, Soong et al. referred to by the discussor as part of this study and found that work to be very useful and informative. This specific research project is part of a comprehensive study by industry collaborators actively involved in the structural design of high-rise buildings with the intent of gaining an understanding of the relationship between nature of ground excitation, ground structure interaction, structural system response and the effective influence of damping systems to mitigate adverse effects. The ultimate aim of this research is to explore the potential for total interactive design that includes ground support, structural framing and the various forms and configurations of damping as an integral part of high-rise building design. In doing so, we believe that it is possible to design not only the dampers but the entire building and its foundations as an integral part of the response reduction mechanism. Hence our focus on the nature of ground excitation and its interactive response with dampers.

This was only possible via a study which involved the numerous parameters that we investigated, such as earthquake type (frequency band and magnitude), damper type, location and configuration, etc. We acknowledge the discussor's comments that "theoretical approaches enable one to capture more essential features of permanent interest", and we plan to continue our work incorporating such an approach combined with synthetic ground excitations to overcome the unpredictability of ground motions.

References

- [Austin and Pister 1985] M. A. Austin and K. S. Pister, "Design of seismic-resistant friction-braced frames", *J. Structural Engineering* **111**:12 (1985), 2751–2769.
- [Aydina et al. 2007] E. Aydina, M. H. Boduroglu, and D. Guney, "Optimal damper distribution for seismic rehabilitation of planar building structures", *Engineering Structures* **29** (2007), 176–185.
- [Drenick 1970] R. F. Drenick, "Model-free design of aseismic structures", *J. Engineering Mechanics Div., ASCE* **96**:EM4 (1970), 483–493.

- [Garcia 2001] D. L. Garcia, "A simple method for the design of optimal damper configurations in MDOF structures", *Earthquake Spectra* **17**:3 (2001), 387–398.
- [Garcia and Soong 2002] D. L. Garcia and T. T. Soong, "Efficiency of a simple approach to damper allocation in MDOF structures", *J. Structural Control* **9**:1 (2002), 19–30.
- [Kiu et al. 2004] W. Kiu, M. Tong, Y. Wu, and G. Lee, "Optimized damping device configuration design of a steel frame structure based on building performance indices", *Earthquake Spectra* **20**:1 (2004), 67–89.
- [Lavan and Levy 2005] O. Lavan and R. Levy, "Optimal design of supplemental viscous dampers for irregular shear-frames in the presence of yielding", *Earthquake Engineering and Structural Dynamics* **34**:8 (2005), 889–907.
- [Lavan and Levy 2006] O. Lavan and R. Levy, "Optimal design of supplemental viscous dampers for linear framed structures", *Earthquake Engineering and Structural Dynamics* **35**:3 (2006), 337–356.
- [Liu et al. 2003] W. Liu, M. Tong, X. Wu, and G. C. Lee, "Object-oriented modeling of structural analysis and design with application to damping device configuration", *J. Computing in Civil Engineering, ASCE* **17**:2 (2003), 113–122.
- [Liu et al. 2005] W. Liu, M. Tong, and G. C. Lee, "Optimization methodology for damper configuration based on building performance indices", *J. Structural Engineering, ASCE* **131**:11 (2005), 1746–1756.
- [Park et al. 2004] J.-H. Park, J. Kim, and K.-W. Min, "Optimal design of added viscoelastic dampers and supporting braces", *Earthquake Engineering and Structural Dynamics* **33**:4 (2004), 465–484.
- [Roberts and Spanos 1990] J. B. Roberts and P. Spanos, *Random vibration and statistical linearization*, John Wiley & Sons, 1990.
- [Shinozuka 1970] M. Shinozuka, "Maximum structural response to seismic excitations", *J. Engineering Mechanics Div., ASCE* **96**:EM5 (1970), 729–738.
- [Silvestri et al. 2003] S. Silvestri, T. Trombetti, and C. Ceccoli, "Inserting the mass proportional damping (MPD) system in a concrete shear-type structure", *Int. J. Structural Engineering and Mechanics* **16**:2 (2003), 177–193.
- [Singh and Moreschi 2001] M. P. Singh and L. M. Moreschi, "Optimal seismic response control with dampers", *Earthquake Engineering and Structural Dynamics* **30**:4 (2001), 553–572.
- [Singh and Moreschi 2002] M. P. Singh and L. M. Moreschi, "Optimal placement of dampers for passive response control", *Earthquake Engineering and Structural Dynamics* **31**:4 (2002), 955–976.
- [Takewaki 1997] I. Takewaki, "Optimal damper placement for minimum transfer functions", *Earthquake Engineering and Structural Dynamics* **26**:11 (1997), 1113–1124.
- [Takewaki 1999] I. Takewaki, "Displacement-acceleration control via stiffness-damping collaboration", *Earthquake Engineering and Structural Dynamics* **28**:12 (1999), 1567–1585.
- [Takewaki 2000a] I. Takewaki, *Dynamic structural design: inverse problem approach*, WIT Press, UK, 2000. 268 pages.
- [Takewaki 2000b] I. Takewaki, "Optimal damper placement for critical excitation", *Probabilistic Engineering Mechanics* **15**:4 (2000), 317–325.
- [Takewaki 2000c] I. Takewaki, "Optimal damper placement for planar building frames using transfer functions", *Structural and Multidisciplinary Optimization* **20**:4 (2000), 280–287.
- [Takewaki 2001] I. Takewaki, "Probabilistic critical excitation for MDOF elastic-plastic structures on compliant ground", *Earthquake Engineering and Structural Dynamics* **30**:9 (2001), 1345–1360.
- [Takewaki 2002a] I. Takewaki, "Critical excitation for elastic-plastic structures via statistical equivalent linearization", *Probabilistic Engineering Mechanics* **17**:1 (2002), 73–84.
- [Takewaki 2002b] I. Takewaki, "Robust building stiffness design for variable critical excitations", *J. Structural Engineering, ASCE* **128**:12 (2002), 1565–1574.
- [Takewaki 2002c] I. Takewaki, "Seismic critical excitation method for robust design: a review", *J. Structural Engineering, ASCE* **128**:5 (2002), 665–672.
- [Takewaki 2004] I. Takewaki, "Bound of earthquake input energy", *J. Structural Engineering, ASCE* **130**:9 (2004), 1289–1297.
- [Takewaki 2007] I. Takewaki, *Critical excitation methods in earthquake engineering*, Elsevier, January 2007.

- [Takewaki and Yoshitomi 1998] I. Takewaki and S. Yoshitomi, "Effects of support stiffnesses on optimal damper placement for a planar building frame", *J. of The Structural Design of Tall Buildings* **7**:4 (1998), 323–336.
- [Takewaki et al. 1999] I. Takewaki, S. Yoshitomi, K. Uetani, and M. Tsuji, "Non-monotonic optimal damper placement via steepest direction search", *Earthquake Engineering and Structural Dynamics* **28**:6 (1999), 655–670.
- [Tan et al. 2005] P. Tan, S. J. Dyke, A. Richardson, and M. Abdullah, "Integrated device placement and control design in civil structures using genetic algorithms", *J. Structural Engineering, ASCE* **131**:10 (2005), 1489–1496.
- [Trombetti and Silvestri 2004] T. Trombetti and S. Silvestri, "Added viscous dampers in shear-type structures: The effectiveness of mass proportional damping", *J. Earthquake Engineering* **8**:2 (2004), 275–313.
- [Trombetti and Silvestri 2006] T. Trombetti and S. Silvestri, "On the modal damping ratios of shear-type structures equipped with Rayleigh damping systems", *J. Sound and Vibration* **292**:1-2 (2006), 21–58.
- [Wongprasert and Symans 2004] N. Wongprasert and M. D. Symans, "Application of a genetic algorithm for optimal damper distribution within the nonlinear seismic benchmark building", *J. Engineering Mechanics, ASCE* **130**:4 (2004), 401–406.
- [Xu et al. 2004] Z. D. Xu, H. T. Zhao, and A. Q. Li, "Optimal analysis and experimental study on structures with viscoelastic dampers", *J. Sound and Vibration* **273**:3 (2004), 607–618.

Received 1 Dec 2006.

JULIUS MARKO: j2.marko@student.qut.edu.au

School of Urban Development, Queensland University of Technology, GPO Box 2434, Brisbane 4001, Australia

DAVID THAMBIRATNAM: d.thambiratnam@qut.edu.au

School of Urban Development, Queensland University of Technology, GPO Box 2434, Brisbane 4001, Australia

NIMAL PERERA: n2nperera@hotmail.com

Robert Bird & Partners, Warwick House, 25 Buckingham Palace Road, London SW1W 0PP, United Kingdom